MODELS

P1610 Color Monitor
Model 633
305708-001

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

SPECIFICATIONS

P1610 Color Monitor

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

Type	Color multiple scan Trinitron			
Picture Tube (diagonal)	24-in Wide Format Trinitron			
Viewable (diagonal)	22.5 in			
Pitch	0.25 to 0.28 mm Aperture Grill Pitch			
Graphic Preset Modes	1920 x 1200 76 Hz	1920 x 1080 60 and 75 Hz	1920 x 1035 60 Hz	1600 x 1200 75 Hz
Note: All modes are non-interlaced unless specified otherwise.	1280 x 1024 75 and 85 Hz	1024 x 768 85 Hz	800 x 600 N/A	640 x 480 60 Hz
Text Mode	720 x 400 70 Hz			
Mac Compatible Modes	1152 x 864	832 x 624		
Note: Adapter required.	N/A	N/A		
User-Programmable Modes	15			
Anti-Glare/Anti-Static	Yes/Yes			
Plug and Play	Yes			
Approvals/Certifications				
MPR-II (Low Emissions)	Yes			
TCO-95	Yes			
Energy Star Compliant	Yes			
UL Approval	Yes			
ISO9241 VOT Guidelines Approval	Yes			
FCC Approval	Yes			
Microsoft PC97 Certified	Yes			
Analog Controls	No			
Brightness, Contrast	Yes			
On-Screen Controls	Yes			
Language Selection				
English	Yes			
Spanish	Yes			
French	Yes			
German	Yes			
Dutch	Yes			
Japanese	Yes			
User Controls				
Sizing and Positioning	Yes			
Pincushion (barrel)	Yes			
Trapezoid	Yes			
Tilt (rotation)	Yes			
Color temperature	Yes			
Degauss	Yes			
Parallelogram	Yes			
Individual color control	Yes			
Overscan (on/off)	N/A			
Pin Balance	Yes			
Moiré Cancellation	Yes			
Convergence	Yes			
Monitor Management	No			
Factory Reset	Yes			
AssetControl	Yes			
Note: When used with Compaq Intelligent Manageability CPUs and appropriate network software				
Pixel Clock Speed	< 245 MHz			
Input Impedance	75 ohms ± 3%			
Horizontal Frequency	30 to 96 kHz			
Vertical Frequency	48 to 160 Hz			
Power Supply ALS	Universal/Auto-Sensing			
Maximum Power Rating	200W			
USB Capabilities	No			
Synch Input	TTL separate synch, composite synch, synch on green			
Signal Cable	15-pin miniature D-sub or 5 BNC Connectors			
Dimensions (HxWxD)	22.8 x 19.7 x 21.6 in/ 58 x 50 x 58.4 cm with base			
Weight	90 lbs/41 kg			

Downloaded from www.Manualslib.com manuals search engine

SPECIFICATIONS *(continued)*

P1610 Color Monitor *(continued)*

Note: AssetControl monitor. AssetControl features are accessible with Compaq desktops featuring Intelligent Manageability.

Temperature	
Operating	60° to 90°F/16° to 32°C
Non-operating	4° to 140°F/–16° to 60°C
Humidity	
Operating	10% to 80%
Non-operating	5% to 95%
ISO9241-3 VDT Guidelines (workplace)	Yes
Warranty	Three-year parts, Three year on-site labor; or Next Business Day direct replacement

Note: Certain restrictions apply. Consult the Compaq Customer Service Support Center for details.

COMPATIBILITY

Portables

Compaq Armada 7800
Compaq Armada 7400
Compaq Armada 6500
Compaq Armada 3500
Compaq Armada 1750
Compaq Armada 1700
Compaq Armada 1500c

Desktops

Compaq Deskpro EN Series Desktop
Compaq Deskpro EN Series Minitower
Compaq Deskpro EN Series Small Form Factor
Compaq Deskpro EP Series

Workstations

Compaq Professional Workstation XP1000
Compaq Professional Workstation AP500

Servers

Compaq ProLiant 7000 Xeon™
Compaq ProLiant 6500 Xeon
Compaq ProLiant 6000 Xeon
Compaq ProLiant 5500 Xeon
Compaq ProLiant 3000 Pentium® III
Compaq ProLiant 3000 6/450
Compaq ProLiant 1600 6/500
Compaq ProLiant 1600 (100 MHz)
Compaq ProLiant 800 (500 MHz)

SMB

Compaq Prosignia Notebook Family of Personal Computers
Compaq Prosignia 740

Downloaded from www.Manualslib.com manuals search engine